

AMENDMENTS TO THE CLAIMS

1. (Previously Amended) An automated apparatus for performing reaction kinetics studies, the apparatus comprising:
 - a plurality of reaction blocks including at least one hot reaction block for heating one or more reaction vessels and at least one cold reaction block for cooling the one or more reaction vessels after heating thereof;
 - a robotic device for transferring one reaction vessel from one hot reaction block to one cold reaction block; and
 - a controller having a user interface for inputting a predetermined temperature profile and a predetermined sampling interval, the controller being in communication with the plurality of reaction blocks and the robotic device so as to instruct the robotic device to transfer one reaction vessel from one hot reaction block to one cold reaction block at a predefined transfer time within the predetermined sampling interval, the predetermined temperature profile representing the temperature of at least one of the hot reaction blocks over a time period of the study;
 - wherein the controller is configured so that both isothermal and nonisothermal temperature profiles can be performed in the same apparatus.
2. (Original) The apparatus of claim 1, wherein each of the hot and cold reaction blocks has a plurality of openings formed therein, one opening receiving one reaction vessel.
3. (Original) The apparatus of claim 1, further including:
 - a heating device associated with each of the hot reaction blocks for controlled heating thereof; and
 - a cooling device associated with each of the cold reaction

reaction vessel when the pressure is applied to the second line with the first line being vented.

10. (Original) The apparatus of claim 8, wherein the gripping mechanism includes a first finger and a second opposing finger with a space therebetween, one reaction vessel being disposed within the space and held between the first and second fingers during the transfer of the one reaction vessel from the hot reaction block to the cold reaction block.
11. (Original) The apparatus of claim 1, wherein the controller includes a master clock and a count-down clock, the master clock displaying the sampling interval for the study and the count-down clock counting down the time before the next transfer of one of the reaction vessels.
12. (Original) The apparatus of claim 1, wherein the master controller includes a user interface for inputting the predetermined temperature profile and the predetermined sampling interval.
13. (Original) The apparatus of claim 1, further including:
 - a temperature control device operatively connected to one or more of the hot and cold reaction blocks for controlling a temperature of each of the hot and cold reaction blocks, the temperature control device being in communication with the controller, and
 - a temperature monitoring device for monitoring the temperature within at least one of the hot and cold blocks, the temperature monitoring device being in communication with the controller so as to provide the controller with temperature data representing the temperature of one or more of the hot and cold blocks.

14. (Previously Amended) The apparatus of claim 13, wherein the temperature control device comprises one of a single loop, dual loop, and multi-loop temperature controller.
15. (Previously Amended) The apparatus of claim 13, wherein the temperature monitoring device is a resistance temperature detector.
16. (Previously Amended) An automated apparatus for performing reaction kinetics studies, the apparatus comprising:
 - a plurality of reaction blocks including at least one hot reaction block for heating one or more reaction vessels and at least one cold reaction block for cooling the one or more reaction vessels after heating thereof;
 - a robotic device for transferring one reaction vessel from one hot reaction block to one cold reaction block; and
 - a controller having a user interface for inputting a predetermined temperature profile and a predetermined sampling interval, the controller being in communication with the plurality of reaction blocks and the robotic device so as to instruct the robotic device to transfer one reaction vessel from one hot reaction block to one cold reaction block at a predefined transfer time within the predetermined sampling interval, the predetermined temperature profile representing the temperature of at least one of the hot reaction blocks over a time period of the study;
 - wherein the predetermined temperature profile is an isothermal temperature profile.
17. (Canceled)
18. (Previously Amended) An automated apparatus for performing reaction kinetics studies, the apparatus comprising:

number of reaction vessels, the hot reaction blocks being connected to one or more heating devices with one or more temperature control devices being associated with the one or more heating devices for setting the temperature of one or more hot reaction blocks and wherein each cold reaction block has a number of openings formed therein for receiving a number of reaction vessels, the cold reaction blocks being connected to one or more cooling devices with one or more temperature control devices being associated with the one or more cooling devices.

20. (Previously Amended) An automated apparatus for performing reaction kinetics studies, the apparatus comprising:

a plurality of reaction blocks including at least one hot reaction block for heating one or more reaction vessels and at least one cold reaction block for cooling the one or more reaction vessels after heating thereof;

a robotic device for transferring one reaction vessel from one hot reaction block to one cold reaction block;

a controller having a user interface for inputting at least (1) a number of reaction vessels for the study, (2) a first predetermined temperature profile and a second predetermined profile, (3) a predetermined study time period beginning with a start time and ending with a stop time, wherein the controller is in communication with the hot and cold reaction blocks and the robotic device, the controller including an operating system which instructs the robotic device to transfer the plurality of reaction vessels from one hot reaction block to one cold reaction block at predefined transfer times and wherein at least one of the hot reaction blocks is heated according to the first predetermined temperature profile over the study time period, the controller collecting and storing kinetics data for each reaction vessel transfer, the kinetics data at least including a temperature of the hot reaction block at each

transfer time and a sampling time when each reaction vessel transfer from the hot reaction block to the cold reaction block occurred; and

wherein the user interface has a first display screen having a first display window where a temperature vs. time graph for the study is displayed and a plurality of a user input display windows which display user inputted information including the predetermined temperature profile and the predetermined study time period and the number of reaction vessels, wherein the first predetermined temperature profile is a nonisothermal temperature profile and the second temperature profile comprises an isothermal temperature profile.

21. (Original) The apparatus of claim 20, wherein the user interface includes a model fit window where a selected model fit program is displayed and the kinetics data is fitted to the desired kinetics model fit program to generate the temperature vs. time graph.
22. (Previously Amended) The apparatus of claim 20, wherein the controller includes a master control display screen having simulated hot and cold reaction block displays which indicate locations of the reaction vessels within each of the hot and cold reaction blocks.
23. (Original) The apparatus of claim 22, wherein the master control display screen has a thermometer display associated with each of the hot and cold reaction blocks, each thermometer display having a graphic thermometer display indicating a temperature of the associated one of the hot and cold reaction blocks and a second display window for numerically indicating the temperature of the associated one of the hot and cold reaction blocks.
24. (Original) The apparatus of claim 20, wherein the robotic device includes a gripping mechanism for gripping and transferring one reaction vessel

from the hot reaction block to the cold reaction block at one of the predefined transfer times.

25. (Original) The apparatus of claim 24, wherein the gripping mechanism includes a first finger and a second opposing finger with a space therebetween, one reaction vessel being disposed within the space and held between the first and second fingers during the transfer of the one reaction vessel from the hot reaction block to the cold reaction block.
26. (Original) The apparatus of claim 24, wherein the controller includes a master clock and a count-down clock, the master clock displaying a remaining time left in the study and the count-down clock displaying a remaining time before the next transfer of one of the reaction vessels.
27. (Previously Amended) The apparatus of claim 1, wherein data associated with a chemical reaction occurring in each reaction vessel is collected and logged as a single data point for display on a corresponding graph.
28. (Previously Amended) A method of performing reaction kinetics studies and collecting data using an automated apparatus, the method comprising:
- providing the automated apparatus, the apparatus including:
 - a plurality of reaction blocks including at least one hot reaction block for heating one or more reaction vessels and at least one cold reaction block for cooling the one or more reaction vessels after heating thereof;
 - a robotic device for transferring one reaction vessel from one hot reaction block to one cold reaction block; and
 - a controller having a user interface and being in communication with the robotic device;

entering a first input using the user interface, the first input corresponding to a number of reaction vessels used in the study;

entering a second input using the user interface, the second input corresponding to an isothermal temperature profile which represents the temperature of at least one of the hot reaction blocks over a time period of the study;

entering a third input using the user interface, the third input corresponding to a nonisothermal temperature profile which represents the temperature of at least one of the hot reaction blocks over a time period of the study;

entering a fourth input using the user interface, the fourth input corresponding to the time period of the study beginning with a start time and ending with a stop time;

transferring the reaction vessels at predefined transfer times, the predefined transfer times being calculated using the first and fourth inputs, each reaction vessel being transferred from one hot reaction block to one cold reaction block by the robotic device which receives command signals from the controller;

collecting kinetics data including at least a temperature of the hot reaction block at each transfer time and a sampling time indicating when each reaction vessel transfer occurred; and

fitting the kinetics data to an inputted kinetics model.

29. (Previously Amended) The method of claim 32, wherein transferring the reaction vessels comprises:

sending a signal from the controller to the robotic device causing a gripping mechanism of the robotic device to be positioned at a predefined coordinate location relative to one of the hot reaction blocks where the gripping mechanism is instructed to securely grasp one of the

reaction vessels, the one reaction vessel then being delivered to one of the cold reaction blocks for storage thereat.

30. (Previously Amended) The method of claim 32, wherein the gripping mechanism includes a first finger and a second finger with a space therebetween, one reaction vessel being disposed within the space and held between the first and second fingers during the transfer, the gripping mechanism being operated by:

 toggling a predetermined pressure between first and second lines, the gripping mechanism closing about the one reaction vessel when the pressure is applied to the first line and the second line is vented, the gripping mechanism being opened to release the one reaction vessel by applying the pressure to the second line with the first line being vented.

31. (Previously Amended) The method of claim 32, wherein the at least one hot reaction block is heated by a heating device, the heating device having a temperature control device and a temperature monitoring device associated therewith, the temperature control device maintaining the temperature of the at least one hot reaction block according to the first input.

32. (Previously Amended) A method of performing reaction kinetics studies and collecting data using an automated apparatus, the method comprising:

 providing the automated apparatus, the apparatus including:

 a plurality of reaction blocks including at least one hot reaction block for heating one or more reaction vessels and at least one cold reaction block for cooling the one or more reaction vessels after heating thereof;

 a robotic device for transferring one reaction vessel

from one hot reaction block to one cold reaction block;

a controller having a user interface and being in communication with the robotic device;

entering a first input using the user interface, the first input corresponding to a number of reaction vessels used in the study;

entering a second input using the user interface, the second input corresponding to a predetermined isothermal temperature profile which represents the temperature of at least one of the hot reaction blocks over a time period of the study;

entering a third input using the user interface, the third input corresponding to a predetermined non-isothermal temperature profile which represents the temperature of another of the hot reaction blocks over a time period of the study;

entering a fourth input using the user interface, the fourth input corresponding to the time period of the study beginning with a start time and ending with a stop time;

transferring the reaction vessels at predefined transfer times, the predefined transfer times being calculated using the first and fourth inputs, each reaction vessel being transferred from one hot reaction block to one cold reaction block by the robotic device which receives command signals from the controller; and

collecting kinetics data including at least a temperature of the hot reaction block at each transfer time and a sampling time indicating when each reaction vessel transfer occurred,

entering a fifth input using the user interface, the fifth input representing a model fit program to which the kinetics data is fitted to generate a representative temperature vs. time graph.

33. (Canceled)

and ending with a stop time;

transferring the reaction vessels at predefined transfer times, the predefined transfer times being calculated using the first and third inputs, each reaction vessel being transferred from one hot reaction block to one cold reaction block by the robotic device which receives command signals from the controller; and

collecting kinetics data including at least a temperature of the hot reaction block at each transfer time and a sampling time indicating when each reaction vessel transfer occurred,

performing multiple kinetics studies in parallel by having at least one hot reaction block and at least one cold reaction block associated with a first run and at least one hot reaction block and at least one cold reaction block associated with a second run, wherein at least one of the first, second and third inputs is different between the first and second runs, wherein the first run is an isothermal run and the second run is a non-isothermal run.

37. (Canceled)